

# Yealink CP925

# Touch-sensitive HD IP conference phone

Yealink CP925 is a touch-sensitive HD conference phone designed for small to medium conference room. CP925 adopts a business and introverted design that perfectly matches the calm style of the conference room, but also a acoustics fabric, which is impervious to any accidental liquid spills. Its fingerprint-proof LCD screen with a clear UI interaction page makes it easy for everyone to control the meeting. CP925 has 7 built-in microphones, providing you with a clear and natural conference call experience. In addition, you can connect CP925 to your mobile device (such as smartphone) via Bluetooth to achieve a hybrid UC meeting.

As a valuable complement for your conference room, Yealink concentrates on users themselves, giving you an easy, clear, and engaging business conference experience.



# **Key features**



4" Multi-Touch Screen



Bluetooth wireless microphone (Optional) \*



Yealink Pentagon meeting room



Hybrid UC meeting



Pairing via Bluetooth

<sup>\*</sup> Wireless Microphone is coming soon

### **Benefits**

## Modest design, easy-to-use user interface

Yealink CP925 is a hermit in the conference room. Its black acoustics fabric can realize crystal-clear audio and is resistant to water, oil, and stain. Its ultra-thin body, appropriate desktop fit, and ingenious hidden wiring slot, perfectly fit for the simple business style in the conference rooms. Additionally, its built-in Linux system and easy-to-use UI interface, allow users to launch a meeting with one button and increase user adoption.

#### HD audio, smooth communication

CP925 adopts Y-shaped design and has 6 built-in microphones for sound pickup and 1 microphone for noise cancellation. Its 20-foot and 360° omnidirection sound pickup provide users with clear and natural voice conference experience.

# Rich features and high expansibility

CP925 supports 5-way conference call, enabling participants from different locations to communicate smoothly, reducing costs for your company. You can also connect CP925 to your mobile devices (such as smart phone, PSTN device CPN10, etc.) through Bluetooth or USB port to realize Hybrid UC meeting (including PSTN, SIP, mobile phone). Moreover, the Bluetooth wireless expansion microphone CPW25 provides 3-meter sound pickup range, which expands the CP925 sound pickup range while still keeping the conference room table clean.

# Yealink SIP-T43U

- 4-inch multi-touch screen with 480x800 resolution
- Optimal HD audio, full duplex technology
- Yealink Noise Proof Technology
- 20-foot (6-meter) and 360-degree voice pickup
- Built-in 6-microphone array for voice pickup
- Built-in 1-microphone array for noise cancellation
- Power over Ethernet
- 5-way conference call
- Hybrid UC meeting
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2
- Local 3-way PSTN conference via Yealink CPN10



# **Specifications**

#### **Audio features**

- Optimal HD audio
- Yealink Noise Proof Technology
- Smart Noise Filtering
- 20-foot (6-meter) microphone pickup range
- Apply to small to medium conference room
- Built-in 6-microphone array, 360-degree voice pickup
- Built-in 1-microphone array, decrease noise
- Loudspeaker
  - Frequency: 100-20,000 Hz
  - Volume: 94dB at 0.5-m peak volume
- 56mm diameter and 5w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- Codecs: G722, G722.1C, G726, G.729, G.729A,
  G723, iLBC, Opus, PCMU (G.711A), PCMA (G.711µ)
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, PLC, AJB, AGC

#### Phone features

- 1 SIP account
- · Call hold, mute, DND, call recording, hotline
- 5-way conference call
- Analog PSTN calls via CPN10
- Redial, call waiting, emergency call
- · Call forward, call transfer, call return, dial plan
- Ring tone selection/import/delete
- Set date time manually or automatically
- Volume adjustment
- Pairing via Bluetooth
- Create meeting directly
- · Join meeting seamlessly
- Active Speaker

#### **Directory**

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- · Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/ forwarded
- Block list

#### **IP-PBX** features

- Busy Lamp Field (BLF)
- Multicast paging
- Intercom
- Anonymous call
- Anonymous call rejection
- Voice mail
- · Distinctive ringtone
- Call pickup

#### **Display**

- 4" 480x800 capacitive touch screen
- Volume key
- Home button

#### **Interface**

- 1 x RJ45 10/100M Ether net por t
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2
- Power over Ethernet (IEEE 802.3af), class 3
- 1 x USB 2.0 Type-C device por t
- 1 x Security slot

#### **Network and Security**

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported

- IPv4/IPv6
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), La yer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Adb encryption authenticated
- Digest authentication using MD5/MD5-sess
- OpenVPN, L2TP VPN
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

# Management

- Configuration: browser/phone/auto-provision/Yealink Device Management Platform
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Reset to factory, reboot

Package tracing export, system log

# Other physical features

- Color: Black
- External Yealink PoE adapter (optional)
- Power consumption (PSU): 3.5W-11W
- Power consumption (PoE): 4W-12W
- Dimension (W\*D\*H): 285mm\*289.5mm\*59.1mm
- Operating humidity: 10~90%
- Storage temperature: -10~40°C (+14~104°F)

## Package features

- Package content:
  - Yealink CP925 IP conference phone
  - Ethernet Cable (7.5m CAT5E UTP cable)
  - M2×5 screw
  - Screwdriver
  - Wireless Microphone CPW25 (Optional)
  - Ouick Start Guide
  - Yealink PoE Adapter YLPOE30 (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 7.036 kg
- G.W/CTN: 8.106 kg
- Giftbox size: 355mm\*349mm\*108mm
- Carton Meas: 567mm\*357mm\*365mm

## Compliance











**ISO 9001** 

For more information, please contact Mayflower on 01277 630444 Visit mayflowerplc.com



Mayflower is a leading provider of business cloud communications and contact center solutions based on its powerful Mayfone platform. More flexible and cost effective than the legacy on-premises PBX and video conferencing systems that it replaces, Mayfone empowers modern mobile and distributed workforces to communicate, collaborate, and connect via any mode, any device, and any location. Mayflower offers three key products in its portfolio including Mayfone, a unified communications as a service (UCaaS) platform including team messaging, video meetings, and a cloud phone system; Mayfone Video, the company's video meetings solution with team messaging that enables Smart Video Meetings; and Mayfone cloud Contact Center solutions. Mayflower's open platform integrates with leading third-party business applications and enables customers to easily customise business workflows.

© 2022 Mayflower Ltd. All rights reserved. Mayflower and the Mayfone logo are registered trademarks of Mayflower Ltd. Other third-party marks and logos displayed in this document are the trademarks of their respective owners.