

Yealink SIP-T57W

Devices and phones



Prime business phone to deliver optimum desktop productivity



Especially designed for busy executives and professionals, Yealink SIP-T57W is an easy-to-use prime business phone with an adjustable 7-inch multi-point touchscreen that offers a rich visual presentation and easy navigation with just one touch. With the built-in Bluetooth 4.2 and dual-band 2.4/5G Wi-Fi, the SIP-T57W IP phone ensures you keep up with modern wireless technology. Its

built-in USB 2.0 port allows for direct wired/wireless USB headsets or up to two Yealink EXP50 expansion module connections. Yealink SIP-T57W is truly a powerful and expandable office phone that delivers optimum desktop efficiency and productivity.



7-inch
Multi-touch
Screen



Adjustable
Screen



Opus Codec



HD Audio



Built-in
Bluetooth



Built-in
Wi-Fi



USB 2.0

Key features and benefits

Outstanding user experience

The Yealink SIP-T57W IP phone features a 7-inch capacitive touchscreen that you can readily adjust to a comfortable viewing angle. Just tap on the smartphone-like interface to easily navigate through menus.

HD audio

The SIP-T57W is coupled with the latest version of the Yealink Optima HD Voice technology, including Yealink Acoustic Shield, that effectively eliminates background distractions and noise while delivering crystal-clear voice.

Hardware

- 7" 800 x 480 capacitive adjustable touchscreen
- Adjustable LCD screen
- Built-in Bluetooth 4.2
- Built-in dual band 2.4G/5G Wi-Fi (802.11a/b/g/n/ac)
- USB 2.0 port for USB recording, wired/wireless USB headsets, and EXP50
- Dual-port Gigabit Ethernet
- PoE support
- Wall mountable

Audio features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield
- Audio codec: Opus, G.722, PCMA, PCMU, G.729A/B, G.726, G.723.1, iLBC
- DTMF: In-band, Out-of-band (RFC 2833), and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJS, AGC

Phone features

- Call hold
- One-touch speed dial
- Hotline
- Call forward, call waiting, call transfer
- Mute, DND
- Emergency call
- Redial, call return
- Auto answer
- 3-way conferencing

- Set date time manually or automatically
- Built-in dual band Wi-Fi:
 - Network standard: IEEE802.11a/b/g/n/ac
 - Transmission rate: Up to 433Mbps (dynamic)
 - Frequency range: 2.4GHz/5.0GHz
- Built-in Bluetooth
- USB port (2.0 compliant) for:
 - Wired/wireless USB headset
 - Color-screen expansion modules EXP50

IP-PBX features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voicemail
- Flexible seating, Executive and Assistant
- Call park, call pickup
- Centralized call recording, call recording

Feature keys

- 7 feature keys: hold, transfer, message, headset, mute, redial, speakerphone
- Volume control keys
- Illuminated mute/headset/hands-free speakerphone key
- Includes 29 touch keys with the ability to display the presence status for up to 27 users on the phone display

Display and indicator

- 7" 800 x 480 capacitive adjustable touchscreen
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and softkeys
- Caller ID with name and number
- Power saving

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af)
- 1 x USB port (2.0 compliant)
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Network and security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP/PPPoE
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS1.2)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6, LLDP/CDP/DHCP VLAN, ICE

Other physical features

- Color: Classic Grey
- Wall mountable (optional)
- External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output

- USB output currency: 5V 500mA
- Power consumption (PSU): 3.2W-6.3W
- Power consumption (PoE): 4.0W-7.8W
- Dimension (W*D*H*T): 259.4mm*220mm*211mm*44.5mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C (+14~122°F)

Package features

- Package content:
 - Yealink SIP-T57W IP phone
 - Handset with handset cord
 - Ethernet cable
 - Stand
 - Power adapter
- Qty/CTN: 5 PCS
- N.W/CTN: 8.86 kg
- G.W/CTN: 9.79 kg
- Giftbox size: 324 mm*293 mm*128 mm
- Carton measurement: 680 mm* 303 mm*342 mm

Compliance



REACH

ISO 9001

For more information, please contact

Mayflower on 01277 630444

Visit mayflowerplc.com



Mayflower is a leading provider of business cloud communications and contact center solutions based on its powerful Mayfone platform. More flexible and cost effective than the legacy on-premises PBX and video conferencing systems that it replaces, Mayfone empowers modern mobile and distributed workforces to communicate, collaborate, and connect via any mode, any device, and any location. Mayflower offers three key products in its portfolio including Mayfone, a unified communications as a service (UCaaS) platform including team messaging, video meetings, and a cloud phone system; Mayfone Video, the company's video meetings solution with team messaging that enables Smart Video Meetings; and Mayfone cloud Contact Center solutions. Mayflower's open platform integrates with leading third-party business applications and enables customers to easily customise business workflows.

© 2022 Mayflower Ltd. All rights reserved. Mayflower and the Mayfone logo are registered trademarks of Mayflower Ltd. Other third-party marks and logos displayed in this document are the trademarks of their respective owners.